

| | | | |
|---------------|--------------------------------|----------------------|---------|
| Designation: | Exterior light / EVML-50 / 19W | Symbol: | |
| Supplier: | Deckma GmbH | Supplier ArtNo.: | 012-044 |
| Manufacturer: | Cortem Group | Manufacturer ArtNo.: | EVML-50 |
| | | Rev: | 0 |

| Electrical data | | | |
|--------------------|-----------|------------------------|-------|
| Voltage [V]: | 220-240 | Current [A]: | |
| Ambient Temp [°C]: | -40 / +40 | Battery backup: | |
| | | Frequency [Hz]: | 50/60 |
| | | Total consumption [W]: | 19 |

| Luminaire description | | | | | |
|-----------------------|---------|-------------------|------|--------------------|------|
| Type: | EVML-50 | Light source: | LED | Consumption [W]: | 17 |
| Technology CC: | | CV: | | Trafo incl.: | |
| | | Illuminant incl.: | | Dimmable: | |
| CRI Index: | 80 | Beam angle [°]: | 120 | No of illuminants: | 1 |
| | | Colour temp [K]: | 5000 | Lum flux [lm]: | 1282 |

| Mechanical description | | | | | |
|------------------------|--|--------------------------------|---------------------------------|----------------------|--------|
| Housing: | low copper / alu alloy | Color: | light grey (RAL7035) | Prot. class: | IP66 |
| Reflector: | | Diffuser: | impact-resistant tempered glass | Fire class: | |
| Surface height [mm]: | | Cover ring: | | Weight [kg]: | 1.10 |
| Rec. mnt. height [mm]: | | Dimens. [mm] L: | 147.00 | W: | 120.00 |
| LED spacing [mm]: | | H: | 163.00 | Ø: | |
| | | LED stripe cutting space [mm]: | | Cut out [mm]: | |
| | | Lum. flux per metre [lm/m]: | | Delivery length [m]: | |
| Mounting: | surface mounted | | | | |
| Equipment: | adjustable mounting bracket, cable gland Nickel plated brass type REV01IB (5-10mm) | | | | |

| Power supply / Dimmer | | | | | |
|-----------------------|--|-------------------|--|----|--|
| Designation: | | | | | |
| Prot. class: | | Dimension [mm] L: | | W: | |
| | | H: | | Ø: | |
| Weight [kg]: | | | | | |
| Designation: | | | | | |
| Prot. class: | | Dimension [mm] L: | | W: | |
| | | H: | | Ø: | |
| Weight [kg]: | | | | | |
| Remarks: | | | | | |

| | |
|----------|---|
| Remarks: | <ul style="list-style-type: none"> - LIGHT.FIXT 120 ° EX II 2GD EX E MB I - compact LED luminaire for medium suspension heights with side M16x1,5 cable entry - tilt degrees for lighting fixture installation EVML-50: 30°, 60° and 90° |
|----------|---|

