

| | | | |
|---------------|-------------------------------------|----------------------|------------|
| Designation: | Floodlight / SLEE-40IM6 50Hz / 400W | Symbol: | |
| Supplier: | Deckma GmbH | Supplier ArtNo.: | 012-050 |
| Manufacturer: | Cortem Group | Manufacturer ArtNo.: | SLEE-40IM6 |
| | | Rev: | 0 |

| Electrical data | | | |
|--------------------|-----------|------------------------|-----|
| Voltage [V]: | 230 | Current [A]: | |
| Ambient Temp [°C]: | -20 / +55 | Battery backup: | |
| | | Frequency [Hz]: | 50 |
| | | Total consumption [W]: | 400 |

| Luminaire description | | | |
|-----------------------|-----------------|--------------------|--------------|
| Type: | SLEE-40IM6 50Hz | Light source: | Metal halide |
| Technology CC: | | Consumption [W]: | 400 |
| CV: | | Dimmable: | |
| Trafo incl.: | | No of illuminants: | 1 |
| ILLuminant incl.: | Y | CRI Index: | |
| Beam angle [°]: | | Colour temp [K]: | |
| | | Lum flux [lm]: | |

| Mechanical description | | | |
|------------------------|--|--------------------------------|----------------------|
| Housing: | low copper / alu alloy | Color: | light grey (RAL7035) |
| Reflector: | anodised aluminium | Prot. class: | IP66/67 |
| Diffuser: | shock resistant tempered glass | Fire class: | |
| Surface height [mm]: | | Weight [kg]: | 27.00 |
| Rec. mnt. height [mm]: | | Dimens. [mm] L: | 480.00 |
| LED spacing [mm]: | | W: | 296.00 |
| | | H: | 482.00 |
| | | Ø: | |
| | | Cut out [mm]: | |
| | | LED stripe cutting space [mm]: | |
| | | Delivery length [m]: | |
| | | Lum. flux per metre [lm/m]: | |
| | | Bend. radius [mm]: | |
| Mounting: | surface mounted / for the connection of the lamp are 2x M25x1,5 to available | | |
| Equipment: | supplied with 1x dummy plug PLG2IG (steel galvanized) | | |

| Power supply / Dimmer | | | |
|-----------------------|--|-------------------|--|
| Designation: | | | |
| Prot. class: | | Dimension [mm] L: | |
| | | W: | |
| | | H: | |
| | | Ø: | |
| | | Weight [kg]: | |
| Designation: | | | |
| Prot. class: | | Dimension [mm] L: | |
| | | W: | |
| | | H: | |
| | | Ø: | |
| | | Weight [kg]: | |
| Remarks: | | | |

Remarks:

- FLOFLOODLIGHT EX II 2GD EX DE IIB + H2 / rectangular headlight / spotlight with swivel bracket
- Ex II 2GD Ex IIB + H2 T3 Ex tD A21 IP66, 230Vac 50Hz; for 400W halogen (E40)
- ballast is integrated in the spotlight housing, capacitor and ignitor are in separate ex-d connection box mounted
- terminals are in a separate Ex-e room safely accommodated

